

Tube Removal Tools

Chipping Hammers & Rivet Busters

Chipping Hammers and Rivet Busters



Beading Chisel

K2LR-RET/K2LH-RET Chipping Hammer

Smallest line of chippers featuring standard .580 hex or .680 round shank bushing. *Parts interchangeable with Ingersoll-Rand K2L models. Please specify 0.580 hex or 0.680 round shank.*

- 1190-1.655 Retainer
- 1194-2 Retainer Spring

Blows Per Minute.....	3600
Stroke.....	1-3/4"
Bore.....	7/8"
Length.....	.12"
Weight.....	8 lbs.
Air Inlet Thread.....	1/4"
Avg. Air Consumption.....	12 cfm



CH SERIES Heavy-Duty Chipping Hammers

Four bolt design eliminates handle breakage. Includes chisel retainer and chisel retainer spring. Aluminum handle model available. *Most parts interchangeable with Sullair CH series chipping hammers. Please specify 0.580 hex or 0.680 round shank.*

- 1190-SUL1 Retainer
- 1194-2 Retainer Spring

Specs	CH2R/ CH2H	CH3R/ CH3H	CH4R/ CH4H
Blows Per Min.	2300	2100	1700
Stroke	3"	3-3/4"	4-1/4"
Bore	1-1/8"	1-1/8"	1-1/8"
Shank Dia.	0.580H/ 0.680R	0.580H/ 0.680R	0.580H/ 0.680R
Length	14-5/8"	16-1/2"	17-1/2"
Weight	17.2 lbs.	18.7 lbs.	19.4 lbs.
Air Inlet	1/2"	1/2"	1/2"
Avg. Air Cons.	31 cfm	35 cfm	39 cfm



CH-ITD SERIES Inside Trigger Chipping Hammers

Inside trigger design for greater comfort and control. Features include plate valve, vibration spacers, rotating exhaust and replaceable inlet bushings. 4-Bolt design reduces handle breakage. *Please specify 0.580 hex or 0.680 round shank.*

- 1190-SUL1 Retainer
- 1194-2 Retainer Spring

Specs	CH2R-ITD/ CH2H-ITD	CH3R -ITD/ CH3H -ITD	CH4R -ITD/ CH4H -ITD
Blows Per Min.	2300	2100	1700
Stroke	3"	3-3/4"	4-1/4"
Bore	1-1/8"	1-1/8"	1-1/8"
Shank Dia.	0.580H/ 0.680R	0.580H/ 0.680R	0.580H/ 0.680R
Length	14"	15-1/4"	16-1/2"
Weight	17 lbs.	18.5 lbs.	19.5 lbs.
Air Inlet	1/2"	1/2"	1/2"
Avg. Air Cons.	31 cfm	35 cfm	39 cfm



EGI 133-NEP EGI 1133-NEP Rivet Buster

Powerful long stroke hammer has the ability to perform all extra heavy-duty demolition applications. Ideal for cutting large rivets, bolts and underground tanks. *Equipped to accept 2000 series jumbo chisels. Model 1133- NEP features a non-ejectable piston.*

Specs	CH2H	CH3H
Capacity	7/8" Rivets	1"
Bore	1-3/16"	1-3/16"
Piston Stroke	8"	11"
Blows Per Minute	960	850
Length	22"	25"
Weight	30 lbs.	34 lbs.
Shank Diameter	1.5"	1.5"
Air Inlet Thread	3/8"	3/8"



EGI 4181-8-USA-NEP EGI 4181-USA-NEP Rivet Buster

Ideal for cutting large rivets, concrete demolition, and heavy-duty chipping work in maintenance and construction. Features a Boyer spool valve to deliver smooth power in any operating position. Equipped to accept 2000 series jumbo chisels.

Specs	4181-8-USA-NEP	4181-USA-NEP
Capacity	7/8" Rivets	1" Rivets
Bore	1-3/16"	1-3/16"
Piston Stroke	8"	11"
Blows Per Minute	1080	720
Length	23"	26"
Weight	31.25 lbs.	34.5 lbs.
Shank Diameter	1.5"	1.5"
Air Inlet Thread	3/8"	3/8"