



DAS II Dominator System

The Airetool DAS II Dominator Rolling Motors are designed to deliver power, performance, and durability while providing accurate and repeatable tube expansion.

- Time proven torque control rolling motors with on-board pneumatic control logic.
- Simple dial-a-torque adjustment collar for easy set up.
- Push-to-start configurations (no suffix) run only when activated, reducing noise and conserving shop air.
- Timed Start* configurations (T suffix) cycle continuously for trigger free tube rolling.
- Tool Options include “Cycle Counter” (C suffix) and “Expander Lubricator” (L suffix).



Examples:

DAS II 1550 900 TCL is a timed start model with counter & lube.

DAS II 850 1250 CL is a push-to-start model with counter & lube.

**Timed Start option will run continuously when the toggle switch is in the “on” position. After the tube is rolled and the tool switches into reverse rotation, an adjustable delay timer is activated. The tool will start running in the forward direction again after the time delay is finished. (Available only on 1050 & 1550 Series.)*

Model Number	Order Number	Free Speed	CFM	Maximum Torque		Minimum Torque		Chucks (in.)†	
		RPM		ft. lbs.	Nm	ft. lbs.	Nm	Included	Optional
DAS II Dominator Rolling Motors*									
DAS II 850 1250 Airetool	8405562	1100	48	9.6	13.0	1.8	2.4	3/8	1/2
DAS II 850 1250 CL Airetool	8405567	1100	48	9.6	13.0	1.8	2.4	3/8	1/2
DAS II 850 600 Airetool	8405569	500	48	16.0	21.7	2.6	3.5	3/8, 1/2	-
DAS II 850 600 CL Airetool	8405578	500	48	16.0	21.7	2.6	3.5	3/8, 1/2	-
DAS II 1050 400 TCL Airetool	8405594	394	68	29.5	40.0	7.5	10.2	3/8, 1/2	3/4 - 1
DAS II 1550 900 Airetool	8405563	756	75	30.7	41.6	4.7	6.4	3/8, 1/2	3/4, 1
DAS II 1550 900 CL Airetool	8405565	756	75	30.7	41.6	4.7	6.4	3/8, 1/2	3/4, 1
DAS II 1550 900 T Airetool	8405576	756	75	30.7	41.6	4.7	6.4	3/8, 1/2	3/4, 1
DAS II 1550 900 TCL Airetool	8405580	756	75	30.7	41.6	4.7	6.4	3/8, 1/2	3/4, 1
DAS II 1550 250 Airetool	8405564	217	75	100.0	135.5	25.0	33.9	3/4, 1	3/8, 1/2
DAS II 1550 250 T Airetool	8405577	217	75	100.0	135.5	25.0	33.9	3/4, 1	3/8, 1/2
DAS II 1550 250 CL Airetool	8405568	271	75	100.0	135.5	25.0	33.9	3/4, 1	3/8, 1/2

† 3/8 & 1/2 are QC Chucks (quick change)

* Configurations

No suffix - Basic Airetool, push-to-start (PTS)

C suffix - PTS with Counter

L suffix - PTS with Lubricator

T suffix - Timer (continuous cycling, negates PTS, available only on 1050 & 1550 Series)